In the claims:

Please amend the claims as follows:

(Currently amended) A water-cooled engine, comprising:
 a cylinder block having a cylinder bore and a water jacket provided about the cylinder bore; and

a cylinder head assembled to the cylinder block, the water-cooled engine being characterized in that:

wherein the cylinder block is divided at the water jacket into a cylinder liner portion and a cylinder outer wall portion, wherein the cylinder liner portion has a wall defining the cylinder bore, and wherein the cylinder outer wall portion surrounds the wall of the cylinder liner portion, thereby defining the water jacket between the cylinder outer wall portion and the wall of the cylinder liner portion, and

wherein the cylinder liner portion includes an upper deck portion integrally formed with the cylinder liner portion, the upper deck portion contacting the cylinder head assembled to the cylinder block, and wherein the cylinder outer wall portion has a top surface that functions as a receiving surface, the receiving surface contacting and supporting the upper deck portion.

- 2. (Currently amended) The water-cooled engine according to claim 1, **eharacterized in that** wherein the cylinder outer wall portion includes a support portion integrally formed with the cylinder outer wall portion, the support portion supporting a lower portion of the cylinder liner portion.
- 3. (Currently amended) The water-cooled engine according to claim 2, eharacterized in that wherein the support portion has a support surface that contacts and supports a lower end of the cylinder liner portion.
- 4. (Currently amended) The water-cooled engine according to claim 2, **characterized in that** wherein the support portion has a support surface that contacts and supports the wall of the cylinder liner portion.

- 5. (Currently amended) The water-cooled engine according to any one of claims 1 to 4, characterized in that claim 1, wherein the cylinder block includes a crankcase portion that is integrally formed with the cylinder outer wall portion.
- 6. (Currently amended) The water-cooled engine according to any one of claims 1-to 5, characterized in that claim 1, wherein the upper deck portion has a through hole that connects a fluid passage formed in the cylinder head with a fluid passage formed in the cylinder outer wall portion.
- 7. (Currently amended) The water-cooled engine according to any one of claims 1 to 6, characterized in that claim 1, wherein, in a state where the upper deck portion is held between a bottom surface of the cylinder head and the receiving surface, the cylinder head and the cylinder outer wall portion are fastened to each other such that the cylinder block is assembled to the cylinder head.
- 8. (Currently amended) A cylinder block of a water-cooled engine, wherein the cylinder block has a cylinder bore and a water jacket provided about the cylinder bore, and is assembled to a cylinder head, the cylinder block being characterized in that:

wherein the cylinder block is divided at the water jacket into a cylinder liner portion and a cylinder outer wall portion, wherein the cylinder liner portion has a wall defining the cylinder bore, and wherein the cylinder outer wall portion surrounds the wall of the cylinder liner portion, thereby defining the water jacket between the cylinder outer wall portion and the wall of the cylinder liner portion, and

wherein the cylinder liner portion includes a substantially planar upper deck portion integrally formed with the cylinder liner portion, the upper deck portion forming a top surface of the cylinder block, and wherein the cylinder outer wall portion has a top surface that functions as a receiving surface, the receiving surface contacting and supporting the upper deck portion.

9. (Currently amended) The cylinder block according to claim 8, **characterized** in that wherein the cylinder outer wall portion includes a support portion integrally formed with the cylinder outer wall portion, the support portion supporting a lower portion of the cylinder liner portion.

- 10. (Currently amended) The cylinder block according to claim 9, **characterized** in that wherein the support portion has a support surface that contacts and supports a lower end of the cylinder liner portion.
- 11. (Currently amended) The cylinder block according to claim 9, **characterized** in that wherein the support portion has a support surface that contacts and supports the wall of the cylinder liner portion.
- 12. (Currently amended) The cylinder block according to any one of claims 8 to 11, characterized by claim 8, further comprising a crankcase portion that is integrally formed with the cylinder outer wall portion.
- 13. (Currently amended) The cylinder block according to any one of claims 8 to 12, characterized in that claim 8, wherein the upper deck portion has a through hole that communicates with a fluid passage formed in the cylinder outer wall portion.
- 14. (Currently amended) The cylinder block according to any one of claims 8 to 13, characterized in that claim 8, wherein the receiving surface of the cylinder outer wall portion has a bolt receiving hole to which a head bolt is threaded, and the upper deck portion has a bolt through hole through which the head bolt is passed.